

## Lubricators Series MC

### Ports G1/4, G3/8 and G1/2 Modular with metal bowl and bayonet-type mounting



The Series MC lubricators are available with ports G1/4, G3/8 and G1/2. The bowls of these lubricators are made of metal and are equipped with a transparent viewer. The oil flow can be monitored through the small transparent cap and regulated by means of the proper adjusting screw.

#### **GENERAL DATA**


Γ								
Construction	modular compact							
Materials	zama, NBR, technopolymer							
Ports	G1/4 G3/8 G1/2							
Oil capacity	cm <sup>3</sup> 37 170 170							
Weight	kg 0,338 0,712 0,674							
Mounting	vertical in-line or wall-mounting							
Operating temperature	-5°C ÷ 50°C at 10 bar (with the dew point of the fluid lower than 2°C at the min. working temperature)							
Oil refilling	without pressure (G1/4) also during use (G3/8 - G1/2)							
Oil for lubrication	from 3°E ÷ 10°E(ask our engineers for types)							
Finishing	enamelled							
Operating pressure	0 ÷ 16 bar							
Nominal flow	see graphs							
Min. air consumption for lubr (NI/min) at 1 bar at 6 bar	G1/4 - G3/8 - G1/2 8 - 8 - 8,5 15 - 17,5 - 15,5							
1								


CODING EXAMPLE									
MC	2	02	-	L	00				
Μ	SERIES								
2	SIZE 1 = G1/4 2 = G3/8 - G1/2								
02	PORTS 04 = G1/4 38 = G3/8 02 = G1/2								
L	L = LUBRICATOR								
00	DESIGN TYPE 00 = atomized oil								

Lubricators Series MC











DIMENSI	ONS

DIMENSIONS														
Mod.	А	В	С	D	E	F	G	Н	Μ	Ν	Р	Q	Т	U
MC104-L00	148	83	40	25	11	107	41	4,5	45	45	37	84	35	G1/4
MC238-L00	187	115	50	22	14	144	43	5,5	62	60	53	117	46	G3/8
MC202-L00	187	115	50	22	14	144	43	5,5	62	60	53	117	46	G1/2

#### FLOW DIAGRAMS






Flow diagram for model: MC104-L00

 $\Delta P$  = Pressure drop Q = Flow

FLOW DIAGRAM



 $\Delta P$  = Pressure drop Q = Flow

# Δp(bar) MC202-LOO 1 2bar 4bar 6bar 8bar 0.8 0.6 0.4

0,4 0,2 0 0 1200 2400 3600 4800 6000 7200 Q (N1/min)

Flow diagram for model: MC202-L00

#### $\Delta P$ = Pressure drop Q = Flow

TREATMENT > Lubricators Series MC

